



PATRIOT MOBILE DIESEL RENTAL: 15KW

The WILDCAT PATRIOT 15KW prime power mobile rental-grade diesel generator is designed to run for extended periods of time as needed and includes a 30 gallon fuel tank and a multi-voltage selector switch.

Durable Industrial Engine

Usually reserved for industrial applications, the power plant is a premier industrial fixed speed (1,800 RPM) engine built to provide strong, reliable power without giving up quiet operation and engine longevity.

Digital Controls

Designed for single genset applications, the digital controls monitor the genset's voltage, current, power, frequency, engine speed, oil pressure and coolant temperature on a back-lit LCD display for ease of use.

Quality Clean Power

Voltage regulation ensures that electronics are safely powered with less 5% total harmonic distortion (THD) at no load.

Industrial Class Alternator

Protected with Class H insulation and standard 40° C nominal rating, the standard 12-wire winding and 2/3 pitch meet all key international standards and regulations.

NFPA-110

Genset is designed to exceed NFPA-110, Level 2 Emergency Power Supply Systems (EPSS) by providing prime power (PP) to meet EPSS Class 168 Type 10.

Easy To Service

Preventative maintenance and in-field repairs are made easier with our simplified engineering and non-proprietary parts.



Engine Make & Model

Kirloskar Oil Engines (KOEL) 3R550

Alternator Make & Model

Leroy Somer LSAP40E

Controller Make & Model

Deep Sea Electronics DSE45XX / 73XX

Weight (Excluding Diesel Fuel)

2,350 lbs 1,066 kgs

Overall Dimensions (in / mm)

120L x 53W x 80H 3048L x 1346W x 2032H

GENERATOR SET RATINGS

Model	Voltage	Power Factor	Phase	Hertz	Circuit Breaker Amps	KW	KVA	BHP	Duty Cycle	Certifications
Patriot Diesel 15 PA0015D4KSXM	120 / 240	1.0	1	60	63	14.3	14.3	23.5	Prime Mobile	EPA Tier 4F
Patriot Diesel 15 PA0015D4KSXM	208 / 120	0.8	3	60	63	15	17	23.5	Prime Mobile	EPA Tier 4F
Patriot Diesel 15 PA0015D4KSXM	240 / 120	0.8	3	60	50	15	17	23.5	Prime Mobile	EPA Tier 4F
Patriot Diesel 15 PA0015D4KSXM	480 / 277	0.8	3	60	25	15	17	23.5	Prime Mobile	EPA Tier 4F

Confidential and proprietary - all rights reserved. © 2025 Engines LPG, LLC dba WILDCAT PowerGen. Use or duplication is expressly prohibited without the express consent of WILDCAT Power Gen.

ENGINE SPECIFICATIONS

Engine

Manufacturer	Kirloskar Oil Engines (KOEL)
Type	3R550 Industrial Powertrain, 4 Cycle, Naturally Aspirated
Speed (RPM)	1800
Cylinder Arrangement	Inline 3
Displacement (L / cc)	1.65L / 1650cc
Bore & Stroke (in / mm)	3.385" x 3.7" / 86 x 94
Compression Ratio	19.7 : 1
Governor Type	Electronic
Frequency Regulation Steady Rate	0.25% (+/-)
Frequency Regulation	Isochronous, Constant Speed
No Load To Full Load	
Air Filter Type	Dry
Limited Warranty	3 Year, 5,000 Hour

Lubrication System

Type	Full Pressure
Oil Capacity (qt / L)	6.23 / 5.95
Oil Filter (Type)	Spin On

Cooling System

Radiator Type	Horizontal Copper Alloy
Fan Type	Pusher

Sound Rating at 7 Meters, Lowest Side

ISO8528-10	Level II
------------	----------

Engine Crankcase Vent System

Engine Crankcase Vent System	Closed Crankcase Vent
------------------------------	-----------------------

Engine Output Deratings

Rated Temperature (°F / °C)	77 / 25
Rated Altitude	3280 ft (1000m) above sea level
Temperature Derate	1.5% for Each 10°F (5.6°C) Above Rated Temperature
Altitude Derate	2.5% for Each 1,000 ft (305m) Above Rated Altitude

Electrical System

Ignition System	Compression Ignition
Battery Quantity	1
Battery Voltage (VDC)	12
Battery CCA (A)	900
Battery Charging Alternator	
Ground (Negative / Positive)	Negative
Voltage (VDC)	12
Amperage (A)	40
Starter Motor Voltage (VDC)	12

Exhaust System

Exhaust Manifold Type	Dry
Exhaust Temp at Rated Load (°F / °C)	1202° F / 650° C
Max Allowable Back Pressure (kPa G)	3.3 +/- 1.0

Fuel System

Fuel Type	Ultra-Low Sulfur Diesel
Fuel Injection Pump	Mechanical Fuel Injection
Fuel Filter	Single Bowl / Spin On
Fuel Tank Size	30 Gallons

Fuel Consumption

	Full Load	50% Load	0% Load
3R550	1.09 gal / hr	0.61 gal / hr	0.31 gal / hr





ALTERNATOR SPECIFICATIONS

Wildcat Model	PA0015D4KSXM	PA0015D4KSXM	PA0015D4KSXM	PA0015D4KSXM
Alternator Model	LSAP 40E	LSAP 40E	LSAP 40E	LSAP 40E
Manufacturer	Leroy Somer	Leroy Somer	Leroy Somer	Leroy Somer
Type	Brushless, 12- Lead	Brushless, 12- Lead	Brushless, 12- Lead	Brushless, 12- Lead
Frequency (Hertz)	60	60	60	60
Phase Voltage	1-Phase 120 / 240	3-Phase 208 / 120	3-Phase 240 / 120	3-Phase 480 / 277
Winding Configuration	Double Delta	Parallel Star	Series Delta	Series Star
Exciter Type	Shunt	Shunt	Shunt	Shunt
Number of Poles	4	4	4	4
Voltage Regulator	R120	R120	R120	R120
Insulation Rating	Class H	Class H	Class H	Class H
Designed Temperature Rise Limit	125 °C	125 °C	125 °C	125 °C
Bearing (Quantity / Type)	1 / Sealed	1 / Sealed	1 / Sealed	1 / Sealed
Coupling	Flexible Disk	Flexible Disk	Flexible Disk	Flexible Disk
Amortisseur Windings	Full	Full	Full	Full
Voltage Regulation, NL to FL	1.0% (+/-)	1.0% (+/-)	1.0% (+/-)	1.0% (+/-)
Total Harmonic Distortion (THD) NL to FL	< 5%	< 5%	< 5%	< 5%

Complete winding protection for non-harsh environment with relative humidity < 95%. IP23 Protection.

Manufactured according to the following standards: ISO 3046, ISO 8528-1, ISO 8528-3, ISO 8528-5, IEC 60034-1, BS 5000-3

CONTROLLER SPECIFICATIONS

Manufacturer	Deep Sea Electronics
Model	DSE 45XX / 73XX
Display	Easy To Read Alpha-Numeric Scrolling Display
Monitoring	Diagnostic Conditions, Fault Codes, Weekly Exercise Cycle

