



ROUGHNECK PRIME GASEOUS: 30KW

The **WILDCAT ROUGHNECK** 30KW prime power stationary gaseous generator is commercial grade and designed to run for extended periods of time as needed.

Durable Industrial Engine

Usually reserved for industrial applications, the power plant is a premier industrial fixed speed (1,800 RPM) engine built to provide strong, reliable power without giving up quiet operation and engine longevity.

Digital Controls

Designed for single genset applications, the digital controls monitor the genset's voltage, current, power, frequency, engine speed, oil pressure and coolant temperature on a back-lit LCD display for ease of use.

Quality Clean Power

Voltage regulation ensures that electronics are safely powered with less 5% total harmonic distortion (THD) at no load.

Industrial Class Alternator

Protected with Class H insulation and standard 40° C nominal rating, the standard 12-wire winding and 2/3 pitch meet all key international standards and regulations.

NFPA-110

Genset is designed to exceed NFPA-110, Level 2 Emergency Power Supply Systems (EPSS) by providing prime power (PP) to meet EPSS Class 168 Type 10.

Easy To Service

Preventative maintenance and in-field repairs are made easier with our simplified engineering and non-proprietary parts.



Engine Make & Model

Arrow Engine Company KP3

Alternator Make & Model

Stamford PI144H

Controller Make & Model

Deep Sea Electronics DSE 61XX

Assembled Weight (lb / kg)

2,761 lbs 1,253 kgs

Overall Dimensions (in / mm)

104L x 44W x 65H 2626L x 1106W x 1647H

GENERATOR SET RATINGS

Model	Voltage	Power Factor	Phase	Hertz	Circuit Breaker Amps	KW	KVA	BHP	Duty Cycle	Certifications
Roughneck NG 30 RO0030NGA*XP	120 / 240	1.0	1	60	125	21	21	30	Prime / Continuous Stationary	EPA Prime Gaseous
Roughneck LP 30 RO0030PLA*XP	120 / 240	1.0	1	60	125	23	23	33	Prime / Continuous Stationary	EPA Prime Gaseous
Roughneck NG 30 RO0030NG**XP	208 / 120 240 / 120 480 / 277	0.8	3	60	100 100 50	25	31	36	Prime / Continuous Stationary	EPA Prime Gaseous
Roughneck LP 30 RO0030PL**XP	208 / 120 240 / 120 480 / 277	0.8	3	60	100 100 50	27	33	39	Prime / Continuous Stationary	EPA Prime Gaseous

Confidential and proprietary - all rights reserved. © 2025 Engines LPG, LLC dba WILDCAT PowerGen. Use or duplication is expressly prohibited without the express consent of WILDCAT Power Gen.

ENGINE SPECIFICATIONS

Engine

Manufacturer	ARROW
Type	KP3 Powertrain, 4 Cycle, Naturally Aspirated
Speed (RPM)	1800
Cylinder Arrangement	Inline 3
Displacement (L / cc)	3.12L / 3120cc
Bore & Stroke (in / mm)	4.10 x 4.70 / 105 x 120
Compression Ratio	9 : 1
Governor Type	Electronic
Frequency Regulation Steady Rate	0.5% (+/-)
Frequency Regulation	Isochronous
No Load To Full Load	
Air Filter Type	Dry
Limited Warranty	3 Year, 5,000 Hour

Lubrication System

Type	Full Pressure
Oil Capacity (qt / L)	8.00 / 7.57
Oil Filter (Quantity / Type)	1 / Spin-On

Cooling System

Radiator Type	Aluminum
Fan Type	Pusher

Sound Rating at 7 Meters, Lowest Side

No Load	70 dB(A)
---------	----------

Air Intake System

Air Filter	Dry Type
------------	----------

Engine Output Deratings

Rated Temperature (°F / °C)	77 / 25
Rated Altitude	1500 ft (457 m) above sea level
Temperature Derate	1.5% for Each 10°F (5.6°C) Above Rated Temperature
Altitude Derate	2.5% for Each 1,000 ft (305m) Above Rated Altitude

Electrical System

Battery Quantity	1
Battery Voltage (VDC)	12
Battery CCA (A)	900
Battery Charging Alternator	
Ground (Negative / Positive)	Negative
Voltage (VDC)	12
Amperage (A)	35
Starter Motor Voltage (VDC)	12

Exhaust System

Exhaust Manifold Type	Dry
Exhaust Temp at Rated Load (°F / °C)	1300° F / 704° C

Fuel System

Fuel Type	Propane or Natural Gas
Fuel Supply Line Inlet	1 1/4" NPT
Fuel Supply Pressure (H2O / mbar)	8 - 16 / 20 - 40

Fuel Consumption

BSFC	Full Load	50% Load	No Load
Pipeline NG	6.40 CFM	3.90 CFM	2.00 CFM
Propane	4.70 GPH	2.80 GPH	1.50 GPH





ALTERNATOR SPECIFICATIONS

Wildcat Model	RO0030**A*XP	RO0030**B*XP	RO0030**C*XP	RO0030**D*XP
Alternator Model	PI144H	PI144H	PI144H	PI144H
Manufacturer	Stamford	Stamford	Stamford	Stamford
Type	Brushless, 12- Lead	Brushless, 12- Lead	Brushless, 12- Lead	Brushless, 12- Lead
Frequency (Hertz)	60	60	60	60
Phase Voltage	1-Phase 120 / 240	3-Phase 208 / 120	3-Phase 240 / 120	3-Phase 480 / 277
Winding Configuration	Double Delta	Parallel Star	Series Delta	Series Star
Exciter Type	Self Exciter	Self Exciter	Self Exciter	Self Exciter
Number of Poles	4	4	4	4
Voltage Regulator	AS480	AS480	AS480	AS480
Insulation Rating	Class H	Class H	Class H	Class H
Designed Temperature Rise Limit	125 °C	125 °C	125 °C	125 °C
Bearing (Quantity / Type)	1 / Sealed	1 / Sealed	1 / Sealed	1 / Sealed
Coupling	Flexible Disk	Flexible Disk	Flexible Disk	Flexible Disk
Amortisseur Windings	Full	Full	Full	Full
Voltage Regulation, NL to FL	1.0% (+/-)	1.0% (+/-)	1.0% (+/-)	1.0% (+/-)
Total Harmonic Distortion (THD) NL to FL	< 5%	< 5%	< 5%	< 5%

Complete winding protection for non-harsh environment with relative humidity < 95%. IP23 Protection.

Manufactured according to the following standards: ISO 3046, ISO 8528-1, ISO 8528-3, ISO 8528-5, IEC 60034-1, BS 5000-3

CONTROLLER SPECIFICATIONS

Manufacturer	Deep Sea Electronics
Model	DSE 61XX
Display	Easy To Read Alpha-Numeric Scrolling Display
Monitoring	Diagnostic Conditions, Fault Codes, Weekly Exercise Cycle

